(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau

national Bureau



(43) International Publication Date 27 February 2003 (27.02.2003)

PCT

(10) International Publication Number WO 2003/016669 A3

(51) International Patent Classification?: 43/00

E21B 19/16,

(21) International Application Number:

PCT/US2002/024399

(22) International Filing Date: 1 August 2002 (01.08.2002)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 60/313,453

20 August 2001 (20.08.2001) US

(71) Applicant (for all designated States except US): EVEN-TURE GLOBAL TECHNOLOGY [US/US]; 16200 A Park Row, Houston, TX 77084 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): WATSON, Brock,

Wayne [US/US]; 2535 Marsh Lane #1004, Carrollton, TX 75006 (US). RING, Lev [RU/US]; 14126 Heatherhill Place, Houston, TX 77077 (US). BRISCO, David, Paul [US/US]; 405 Westridge Drive, Duncan, OK 73533 (US).


(74) Agents: MATTINGLY, Todd et al.; Haynes and Boone, LLP, Suite 4300, 1000 Louisiana Street, Houston, TX 77002-5012 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW). Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM).

[Continued on next page]

(54) Title: APPARATUS FOR RADIALLY EXPANDING TUBULAR MEMBERS INCLUDING A SEGMENTED EXPANSION CONE



(57) Abstract: An apparatus for radially expanding tubular members including a segmented expansion cone.

European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

- of inventorship (Rule 4.17(iv)) for US only

Published

with international search report

(88) Date of publication of the international search report: 10 June 2004

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US02/24399

A. CLASSIFICATION OF SUBJECT MATTER IPC(7) : E21B 19/16; 43/00			
US CL : 166/380, 207			
According to International Patent Classification (IPC) or to both national classification and IPC			
B. FIEL	DS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols) U.S.: 166/380, 207, 209, 212, 216, 217			
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched			
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)			
C DOCK CONCONCIDED TO BE DELEVANT			
	UMENTS CONSIDERED TO BE RELEVANT		
Category *			Relevant to claim No.
Х	US 4,420,866 A (MUELLER) 20 December 1983 (20.12.83), figure 1.		1, 6, 8, 11, 13
Y			4
х	US 6,085,838 A (VERCAEMER et al.) 11 July 2000 (11.07.00), figures 5-7.		8
	05 0,065,056 A (VERCALIVIER et al.) 11 July 2000 (11.07.00), liguies 5-7.		
Y			4
•			
			1
			Į.
Ì			
\			
	•		
1			
Further	documents are listed in the continuation of Box C.	See patent family annex.	
	pecial categories of cited documents:	"T" later document published after the inte	rnational filing date or priority
date and not in conflict with the application but cited to understand the			
"A" document defining the general rate of the art which is not considered to be principle or theory underlying the invention			
or particu	ilar relevance	"X" document of particular relevance; the	claimed invention cannot be
"E" carlier ap	oplication or patent published on or after the international filing date	considered novel or cannot be conside when the document is taken alone	
*L" document which may throw doubts on priority claim(s) or which is cited to			
	the publication date of another citation or other special reason (as	"Y" document of particular relevance; the considered to involve an inventive ste	
specified		combined with one or more other suc	
"O" document referring to an oral disclosure, use, exhibition or other means		being obvious to a person skilled in the	
· Cocuman persons prior to an instrument		"&" document member of the same patent	family
priority date claimed			
Date of the actual completion of the international search		Date of mailing of the international sear	ch report
24 September 2002 (24.09.2002)			
Name and mailing address of the ISA/US Anthorized Officer			
Commissioner of Patents and Trademarks Box PCT David Bagnett			
	shington, D.C. 20231	1	
Facsimile No. (703)305-3230 Telephone No. (703) 308-1113			

Form PCT/ISA/210 (second sheet) (July 1998)

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

Organization
International Bureau



(43) International Publication Date 27 February 2003 (27.02.2003)

PCT

(10) International Publication Number WO 2003/016669 A3

(51) International Patent Classification⁷: 43/00

E21B 19/16,

(21) International Application Number:

PCT/US2002/024399

(22) International Filing Date: 1 August 2002 (01.08.2002)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/313,453

20 August 2001 (20.08.2001) US

(71) Applicant (for all designated States except US): EVEN-TURE GLOBAL TECHNOLOGY [US/US]; 16200 A Park Row, Houston, TX 77084 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): WATSON, Brock,

Wayne [US/US]; 2535 Marsh Lane #1004, Carrollton, TX 75006 (US). RING, Lev [RU/US]; 14126 Heatherhill Place, Houston, TX 77077 (US). BRISCO, David, Paul [US/US]; 405 Westridge Drive, Duncan, OK 73533 (US).


(74) Agents: MATTINGLY, Todd et al.; Haynes and Boone, 1.I.P, Suite 4300, 1000 Louisiana Street, Houston, TX 77002-5012 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: APPARATUS FOR RADIALLY EXPANDING TUBULAR MEMBERS INCLUDING A SEGMENTED EXPANSION CONE



(57) Abstract: An apparatus for radially expanding tubular members including a segmented expansion cone.

European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BIF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

Published:

with international search report

with amended claims

(88) Date of publication of the international search report: 10 June 2004

Date of publication of the amended claims: 26 August 2004

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

AMENDED CLAIMS

[received by the International Bureau on 19 April 2004 (19.04.2004); new claims 22-45 added; remaining claims unchanged (6 pages)]

arcuate conical expansion cone segments interleaved among the longitudinal slots;

an actuator for adjusting the tubular adjustable expansion cone, comprising:

- a first tubular member coupled to the adjustable tubular expansion cone defining a plurality of first radial passage and comprising a plurality of internal flanges interleaved among the first radial passages;
- a second tubular member received within the first tubular member defining a plurality of second radial passages interleaved among the first radial passages and comprising a plurality of external flanges interleaved among the first and second radial passages and the internal flanges; and a tubular expansion cone coupled to the second tubular member for radially expanding the tubular adjustable expansion cone.
- 20. A method of plastically deforming and radially expanding a tubular member, comprising:

 positioning an adjustable tubular expansion cone within the tubular member; and
 increasing the size of the adjustable tubular expansion cone within the expandable tubular member,
 comprising:

 positioning a tubular segmented expansion cone within the tubular member;
 positioning a tubular expansion cone within the tubular member; and
 displacing the tubular expansion cone relative to the tubular segmented expansion cone.
- An apparatus for plastically deforming and radially expanding a tubular member, comprising:

 means for positioning an adjustable tubular expansion cone within the tubular member; and

 means for increasing the size of the adjustable tubular expansion cone within the expandable tubular

 member, comprising:

 means for positioning a tubular segmented expansion cone within the tubular member;

 means for positioning a tubular expansion cone within the tubular member; and

 means for displacing the tubular expansion cone relative to the tubular segmented expansion

 cone.
- 22. An apparatus for forming a wellbore casing within a wellbore within a subterranean formation, comprising: a tubular support member;

an adjustable expansion device coupled to the tubular support member;

an actuator coupled to the tubular support member for adjusting the circumferential size of a segmented outer surface of the adjustable expansion device;

an expandable tubular member coupled to the tubular support member defining a longitudinal passage for receiving the tubular support member, the adjustable expansion device, and the actuator; and

one or more sealing members for sealing the interface between the tubular support member and the expandable tubular member.

23. The apparatus of claim 22, wherein the adjustable expansion device comprises: a tubular body defining a plurality of longitudinal slots and comprising a plurality of internal arcuate expansion segments interleaved among the longitudinal slots.

- 24. The apparatus of claim 22, wherein the actuator comprises:
 - a first tubular member coupled to the tubular support member defining a plurality of first radial passage and comprising a plurality of internal flanges interleaved among the first radial passages;

a second tubular member received within the first tubular member defining a plurality of second radial passages interleaved among the first radial passages and comprising a plurality of external flanges interleaved among the first and second radial passages and the internal flanges; and an expansion device coupled to the second tubular member for radially expanding the adjustable expansion device.

25. A method of forming a wellbore casing within a wellbore within a subterranean formation, comprising: positioning an expandable tubular member and an adjustable expansion device within the wellbore;

increasing the circumferential size of a segmented outer surface of the adjustable expansion device within the expandable tubular member; and

plastically deforming and radially expanding the expandable tubular member using the adjustable expansion device.

26. The method of claim 25, wherein increasing the size of the adjustable expansion device within the expandable tubular member comprises:

positioning a segmented expansion device within the expandable tubular member; positioning an expansion device within the expandable tubular member; and displacing the expansion device relative to the segmented expansion device.

27. An apparatus for forming a wellbore casing within a wellbore within a subterranean formation, comprising: means for positioning an expandable tubular member and an adjustable expansion device within the wellbore;

means for increasing circumferential size of a segmented outer surface of the adjustable expansion device within the expandable tubular member; and

means for plastically deforming and radially expanding the expandable tubular member using the adjustable expansion device.

28. The apparatus of claim 27, wherein the means for increasing the size of the adjustable expansion device within the expandable tubular member comprises:

means for positioning a segmented expansion device within the expandable tubular member; means for positioning an expansion device within the expandable tubular member; and

means for displacing the expansion device relative to the segmented expansion device.

29. An adjustable expansion device for plastically deforming and radially expanding a tubular member, comprising:

an adjustable tubular expansion device; and an actuator for adjusting the tubular adjustable tubular expansion device.

- 30. The adjustable expansion device of claim 29, wherein the adjustable tubular expansion device comprises: a tubular body defining a plurality of longitudinal slots and comprising a plurality of internal arcuate expansion segments interleaved among the longitudinal slots.
- 31. The adjustable expansion device of claim 29, wherein the actuator comprises:

a first tubular member coupled to the adjustable expansion device defining a plurality of first radial passage and comprising a plurality of internal flanges interleaved among the first radial passages; a second tubular member received within the first tubular member defining a plurality of second radial passages interleaved among the first radial passages and comprising a plurality of external flanges interleaved among the first and second radial passages and the internal flanges; and

an expansion device to the second tubular member for radially expanding the tubular adjustable expansion device.

- 32. A method of plastically deforming and radially expanding a tubular member, comprising:

 positioning an adjustable expansion device within the tubular member; and

 increasing circumferential size of a segmented outer surface of the adjustable expansion

 device within the expandable tubular member.
- 33. The method of claim 32, wherein increasing the size of the adjustable expansion device within the tubular member comprises:

positioning a segmented expansion device within the tubular member; positioning an expansion device within the tubular member; and displacing the expansion device relative to the segmented expansion device.

- 34. An apparatus for plastically deforming and radially expanding a tubular member, comprising: means for positioning an adjustable expansion device within the tubular member; and means for increasing the circumferential size of a segmented outer surface of the adjustable expansion device within the expandable tubular member.
- 35. The apparatus of claim 34, wherein the means for increasing the size of the adjustable expansion device within the tubular member comprises:

means for positioning a segmented expansion device within the tubular member; means for positioning an expansion device within the tubular member; and means for displacing the expansion device relative to the segmented expansion device.

36. An apparatus for forming a wellbore casing within a wellbore within a subterranean formation, comprising: a tubular support member;

an adjustable expansion device coupled to the tubular support member, comprising:

a body defining a plurality of longitudinal slots and comprising a plurality of internal expansion segments interleaved among the longitudinal slots;

an actuator coupled to the tubular support member for adjusting the size of the adjustable expansion device, comprising:

a first tubular member coupled to the tubular support member defining a plurality of first radial passage and comprising a plurality of internal flanges interleaved among the first radial passages;

a second tubular member received within the first tubular member defining a plurality of second radial passages interleaved among the first radial passages and comprising a plurality of external flanges interleaved among the first and second radial passages and the internal flanges; and

an expansion device coupled to the second tubular member for radially expanding the adjustable expansion device;

a shoe releasably coupled to the adjustable expansion device;

an expandable tubular member coupled to the shoe defining a longitudinal passage for receiving the tubular support member, the adjustable expansion device, and the actuator; and one or more sealing members for sealing the interface between the tubular support member and the expandable tubular member.

37. A method of forming a wellbore casing within a wellbore within a subterranean formation, comprising:

positioning an expandable tubular member and an adjustable expansion device within the

wellbore;

increasing the size of the adjustable expansion device within the expandable tubular member, comprising:

positioning a segmented expansion device within the expandable tubular member; positioning an expansion device within the expandable tubular member; and displacing the expansion device relative to the segmented expansion device; and plastically deforming and radially expanding the expandable tubular member using the adjustable expansion device.

38. An apparatus for forming a wellbore casing within a wellbore within a subterranean formation, comprising:

means for positioning an expandable tubular member and an adjustable expansion device

within the wellbore;

means for increasing the size of the adjustable expansion device within the expandable tubular member, comprising:

means for positioning a segmented expansion device within the expandable tubular member; means for positioning an expansion device within the expandable tubular member; and means for displacing the expansion device relative to the segmented expansion device; and means for plastically deforming and radially expanding the expandable tubular member using the adjustable expansion device.

39. An adjustable expansion device for plastically deforming and radially expanding a tubular member, comprising:

an adjustable tubular expansion device, comprising:

adjustable tubular expansion device.

a tubular body defining a plurality of longitudinal slots and comprising a plurality of internal expansion segments interleaved among the longitudinal slots; and

an actuator for adjusting the adjustable tubular expansion device, comprising:

a first tubular member coupled to the adjustable tubular expansion device defining a plurality of first radial passage and comprising a plurality of internal flanges interleaved among the first radial passages;

a second tubular member received within the first tubular member defining a plurality of second radial passages interleaved among the first radial passages and comprising a plurality of external flanges interleaved among the first and second radial passages and the internal flanges; and an expansion device coupled to the second tubular member for radially expanding the

40. A method of plastically deforming and radially expanding a tubular member, comprising: positioning an adjustable tubular expansion device within the tubular member; and increasing the size of the adjustable tubular expansion device within the expandable tubular member, comprising:

positioning a tubular segmented expansion device within the tubular member; positioning an expansion device within the tubular member; and displacing the expansion device relative to the segmented expansion device.

41. An apparatus for plastically deforming and radially expanding a tubular member, comprising:

means for positioning an adjustable expansion device within the tubular member; and

means for increasing the size of the adjustable expansion device within the expandable tubular

member, comprising:

means for positioning a segmented expansion device within the tubular member; means for positioning an expansion device within the tubular member; and means for displacing the expansion device relative to the segmented expansion device.

42. A method of radially expanding and plastically deforming a tubular member, comprising: positioning an adjustable expansion device within the tubular member, adjusting a size of the adjustable expansion device within the tubular member, and displacing the adjustable expansion device relative to the tubular member by pulling the adjustable expansion device through the tubular member using fluid pressure.

- 43. A system for radially expanding and plastically deforming à tubular member, comprising: means for positioning an adjustable expansion device within the tubular member; means for adjusting a size of the adjustable expansion device within the tubular member; and means for displacing the adjustable expansion device relative to the tubular member by pulling the adjustable expansion device through the tubular member using fluid pressure.
- 44. A method of radially expanding and plastically deforming a tubular member, comprising: positioning an expansion device within the tubular member; and displacing the expansion device relative to the tubular member by pulling the expansion device through the tubular member using fluid pressure.
- 45. A system for radially expanding and plastically deforming a tubular member, comprising: means for positioning an expansion device within the tubular member; and means for displacing the expansion device relative to the tubular member by pulling the expansion device through the tubular member using fluid pressure.